

an interlayer insulating film interposed between the active matrix substrate and the plurality of pixel electrodes, wherein one of said two layers has a first porous surface and the other one of said two layers has a second porous surface, and said two layers have concavities and convexities.

8. (Amended) A reflection type liquid crystal display device comprising:

at least one thin film transistor formed over an active matrix substrate;

a pixel electrode connecting to said thin film transistor;

an interlayer insulating film formed between said thin film transistor and said pixel electrode;

a light reflective film formed of at least two layers on said pixel electrode, wherein an upper surface of said light reflective film is porous, and has concavities and convexities;


a first orientation film formed at least on said light reflective film;

a color filter comprising red, green and blue [formed over] adjacent to an opposing substrate;

an opposing electrode [formed over] adjacent to said opposing substrate;

porous surface

kon - kon



2 a second orientation film [formed over] adjacent to
said opposing substrate; and
a liquid crystal material injected between said first
and second orientation film[,
[wherein said reflection type liquid crystal display
device has a reflectance of 80 % or less].

Sub FI 3 11. (Amended) A liquid crystal display device of claim 8,
wherein [said] a reflectance is 70 % or more when an applied
voltage is 5V to 15V.

Sub D4 14. (Amended) A reflection type liquid crystal display
device comprising:
a thin film transistor [on] over a substrate having an
insulating surface;
an interlayer insulating film comprising a material
selected from the group consisting of silicon oxide, silicon
nitride and an organic resin on said thin film transistor;
a pixel electrode connected to said thin film
transistor; and
a light reflective film formed of at least two layers
on said pixel electrode,

Q
wherein one of said two layers has a first porous surface and the other one of said two layers has a second porous surface, and said two layers have concavities and convexities [, and

[wherein said reflection type liquid crystal display device has a reflectance of 80 % or less].

Sub F1
18. (Amended) A liquid crystal display device of claim 14, wherein [said] a reflectance is 70 % or more when an applied voltage is 5V to 15V.

Sub D4
19. (Amended) A reflection type liquid crystal display device comprising:
at least one thin film transistor formed over an active matrix substrate;
a pixel electrode connecting to said thin film transistor;
an interlayer insulating film formed between said thin film transistor and said pixel electrode;
a light reflective film formed on said pixel electrode, wherein an upper surface of said light reflective film is porous, and has concavities and convexities;

a first orientation film formed at least on said light reflective film;

a color filter comprising red, green and blue [formed over] adjacent to an opposing substrate;

an opposing electrode [formed over] adjacent to said opposing substrate;

a second orientation film [formed over] adjacent to said opposing substrate; and

a liquid crystal material injected between said first and second orientation film.

23. (Amended) A reflection type liquid crystal display device comprising:

a thin film transistor [on] over a substrate having an insulating surface;

an interlayer insulating film comprising a material selected from the group consisting of silicon oxide, silicon nitride and an organic resin on said thin film transistor;

a pixel electrode connected to said thin film transistor; and

a light reflective film formed on said pixel electrode,